

HSRoute® Thinner

Description of product	Cleaning agent on the basis of organic solvents and thinner for solvent borne road marking paints.
Area of application	To be used for thinning of solvent borne road marking paints up to 3 % by weight and as cleaning agent for tools and application equipment. <i>Not to be used for thinning of cold plastic materials and cold spray plastic!</i>
Technical characteristics	
Chemical composition:	Mixture of organic solvents acetone, 2-butanone (MEK) and 2-methyl-pentane-2-one (MIBK)
Colour:	Clear
Density:	0.80 ± 0.04 kg/l
VOC-content:	100.0 % (798 g/l) (according to VOC-guideline 2004/42/EG)
Additional information:	Free from aromatic hydrocarbons Information regarding current legal prescriptions and relevant safety requirements are part of the Material Safety Data Sheet (MSDS) which has to be read and understood before using the product. The MSDS also contains important information regarding transport, use and handling, storage, disposal and information regarding first aid, toxicology and ecology.
Storage stability:	Unlimited, when kept in the original packaging under proper storage conditions.
Storage:	Store in tightly closed original containers in a dry, well-ventilated room at temperatures up to max. +30 °C, not directly on the floor and not in the vicinity of heating radiators.
Packaging:	Metal canister with 22.0 kg net.

GEVEKO PRODUCTION • PLASTIROUTE

Spezialfarben für Horizontal-Markierungen GmbH
Renkenrungsstraße 16
79379 Müllheim/Baden • Germany
Phone: +49 7631 3687-0
Fax: +49 7631 368736

info@plastiroute.de
www.plastiroute.de

This information was compiled to the best of our knowledge, based on lab tests and practical experience. Since the product is processed under conditions that are beyond our control, we can only guarantee the quality of the product. The information provided here is not to be deemed a warranty as to quality. We reserve the right to modify the information within the scope of existing approvals.