

Product Technical Specification

Commercial Name	UCme 850-180MP
Old Specification Number	30021, 50, 111
Product Type	Drop on Glass Bead
Standard	EN1423
CE Certification	1137-CPR-0484/81
DOP	DOP 451015-16/451021-16/451043-16
Benor Certification	N/A
Kitemark Certification	KM522541

Micron Size	Retained %	Cumulative Retained %	Passing %
1000		0-2	
850		0-10	
500		20-40	
425		35-55	
300		65-85	
180		95-100	

Roundness	>80%	Testing Method	Image Analyser
Glass Characteristic	Soda Lime Glass	Refractive Index	Class A: >1.5
Dangerous Substance	According EN1423	Coating Process	MP (moisture resistance)
Desiccating Agent	N/A	Sample Retention	12 Months
Shelf Life	12 Months	Safety Advice	See MSDS

Customer	Country	D365 Item Number	Customer Identifier	Pallet Size	Packaging Variants	Special Requirements
GMSE	Sweden	451015	460001	1000kg	25kg UCme WP/Euro Pallet	Rain Hood
GMSE	Sweden	451021	460002	1200kg	300kg*4/UK Std Pallet	Rain Hood
Rikiskaup	Iceland	451021	460002	1200kg	300kg*4/UK Std Pallet	Rain Hood
GMUK	UK	451043	N/A	1000kg	25kg WP/UK Std Pallet	N/A

